

Technical Data – Full-Body Harnesses

Certification:	Fully complies with ANSI A10.32, 2004 and ANSI Z359.1, 2007 standards and all OSHA requirements, including 1910.66 Appendix C and 1926 Subpart M, and CSA Z259.
Description:	A full-body fall arrest harness offering lightweight webbing, leg adjustments, chest strap, back sliding D-ring for fall protection and semi-universal sizing
Identification:	Identification is made by a tag attached to the harness stating manufacturer, date of manufacture, model and serial number.
Material of Construction:	Webbing: 1 3/4 in. (44 mm) Nylon webbing D-rings: Stamped steel D-ring with minimum tensile strength of 5,000 lb (2,268 kg). The D-ring is cad or zinc plated and meets the ASTM fifty-hour salt spray test requirements. 100% proof tested
Load Limit:	1 Worker (310 lb [140.6 kg] – person, tools, etc.)
Weight:	3-5 lb (1.4-2.3 kg), depending on model
Warranty:	All Spider harnesses are warranted against any defects in workmanship and materials for a period of one year from the date of purchase when purchased in the United States. This warranty does not cover damage caused by accident, abuse, misuse or an act of God (such as a flood). Consequential and incidental damages, including without limitation, loss of property and those arising from breach of any express or implied warranty, are not the responsibility of Spider and, to the extent permitted by law, are excluded.

Call or click for more information
1-877-774-3370
www.spiderstaging.com